

Declaration of performance 202 -Tuplex LVT-16/01/2020

Unique identification of the product type:

Tuplex LVT

Intended use:

Underlay of the laminate floor coverings

Manufacturer:

Jackon Finland Oy, Toravantie 18, 38210 Sastamala, Finland.
Tel. + 358 10 8419200, www.jackon.fi

Testing laboratory:

Tampere University of Technology
Department of Civil Engineering and Material Science, P.O. Box 600 33101 Tampere
Finland, Research report No. 2444

Declared performances:

Essential characteristics	Performance		Harmonised technical specification
Nominal thickness	Thickness	1,1 mm	EN 16354:2018
Width	w _d	1100 +200 mm	
Length	l _d	15 / 30 m	
Squareness	q _{max}	< 5 mm/m	
Flatness	s _{max}	< 2 mm/m	
Area weight	AW	120 gr/m ²	
Water vapour permeability	Water vapour transmission	NPD	
Compressive strength	Compressive stress at 10% deformation (CS2)	200 kPa	
Compressive creep	CC1	≥ 5 kPa	
Punctual conformability	PC2	1,1 mm	
Dynamic load resistance	DL2	100.000 ... 200.000	

NPD = no performance determined;

The performance of the product identified above is in conformity with the set of declared performances. The declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Sastamala 22.01.2020

Veli Ollila, managing director



Veli Ollila